

AC TWIN CAPSTAN WINCH

CE



Safe, infinitely controllable pulling, holding and lowering out with the [Goodwinch AC Twin Capstan winch](#). Variable speed from hold, through creep to full speed of approximately 10 metres per minute.

Ideal for pulling cables through ducts, raising portable buildings, pulling roof covers over temporary and permanent structures and other similar pulling and lowering activities. Work from either side to suit the application.

The main capstan gearbox, along with the capstan bollards, are driven through an Hydrostatic speed variator which allows variable bollard revolutions from the AC motor. Variable speeds of the bollards from hold, through creep to full speed is achieved by moving the lever at the top of the hydrostatic variator.

The winch is supplied in 110 volts AC rated at 2HP (1.5Kw).

We fit 4 pole motors @ 1,400 rpm giving a maximum of 32 rpm of the bollards pulling in 10 metres (33') per minute.

Designed by David Bowyer and manufactured by

GOODWINCH LIMITED

East Foldhay, Zeal Monachorum, Crediton,
Devon, EX17 6DH, England

Tel: 01363 82666

Fax: 01363 82782

E.MAIL: sales@goodwinch.com

WEBSITE: www.goodwinch.com

We also supply a wide range of Superwinch electric and hydraulic winches up to 13.6 tonne pull for emergency vehicles. All can be seen on our website www.goodwinch.com



AC TWIN CAPSTAN WINCH

SPECIFICATIONS

Twin Capstans	Aluminium, 100mm diameter
Capstan gearbox	Worm and Wheel, 30:1 ratio
Hydraulic variable gearbox	Hydrostatic speed variator
Speed change.....	Lever control
AC motor in 110 volts	2HP (1.5kw)

PERFORMANCE

Method of starting and Emergency stopping	To be installed by Site Electrician
Bollard speed control	Lever on top of variator
Load retrieval speed	Creep to 10m per minute (4 pole motors) Creep to 20m per minute (2 pole motors)
Pulling capacity	Maximum 325 kgs (700lb)
Recommended duct rope	6 - 10mm
Suitable rope length	As required, no maximum

DIMENSIONS

Whole unit	70cm long x 39cm wide x 42cm high
Approx. overall weight	60 kgs

