


**GOODWINCH Ltd** also stock this very powerful TDS 10,000 lbs (4,535 Kgs) commercial hydraulic winch, which is very efficient and suitable for use with either wire rope or synthetic Dyneema® Bowrope



**The KHD-10 Goldfish Series**

**2 Ratio Variable Speed Hydraulic Winch pulling a load with the vehicle held in place with a set of ChocTracks**



**FEATURES**

- Smooth running over the entire speed range
- Highly efficient, constant operating torque motor
- Rotating ring gear freespool clutch operated by pull and turn for rapid rope payout
- Freespooling. Power in /out. Hydraulic Lock
- Stainless Steel Tie Bars
- Reversible mounting
- Supplied as a bare winch, for your choice of rope and fairleads

Defender Special Bumper **£199 + VAT**

Bright Zinc Plated Swivel Recovery eyes with tested shackles (pair) **£30 + VAT**

KHD-10 bare winch (no rope or fairleads)

**£ 699 + VAT**

KHD-10 complete with 9.5mm x 27m wire rope and roller fairleads

**£ 739 + VAT**

KHD-10 complete with 11mm x 27m Dyneema® Bowrope & Aluminium Hawse

**£ 864 + VAT**

Defender (TD5 only) PTO (off gearbox), pump, selector mechanism, tank (under offside floor) filler, all hoses and control valves

**£3,247 + VAT**

Lodar Wireless Radio Remote

**£ 179 + VAT**

High Quality Aluminium ChocTracks with adjustable ground spades designed to hold a vehicle in place while winching. **£249 + VAT**

**GOODWINCH LIMITED**

East Foldhay, Zeal Monachorum, CREDITON,  
Devon, EX17 6DH, England

**Tel: 01363 82666**

**Fax: 01363 82782**

**E: sales@goodwinch.com**

**W: www.goodwinch.com**

AS MOST OF OUR BUSINESS IS UK & EUROPEAN 4x4 DEALERS AND OVERSEAS SALES, ALL PRICES ARE PLUS CARRIAGE AND VAT

Simply brilliant, our versatile light weight, easy to splice and handle

**DYNEEMA® BOWROPE**

An immensely strong 12 strand synthetic winch rope made from Dyneema® SK75 High Modulus Polyethylene Fibre, manufactured to a very high exact specification set by David Bowyer of GOODWINCH LIMITED



**Importers, Exporters, Wholesale Distributors and Retailers of Winches & Accessories**

Dyneema® is a registered trademark of Royal DSM N.V.

## Specification

Model	KHD-10
Line Pull	HIGH 1,667lb / 756kg
	LOW 10,000 / 4,535kg
Operation Pressure	175 bar / 2537 psi
Max Oil Flow	15.9 g/min (60 l/min)
Gear Ratio	FREE
	1:1 (HIGH)
	1:6 (LOW)
Wire Rope Size	9.5mm x 27.4m (3/8" x 90')
Drum Size	63.5mm x 215mm (2.5" x 8.4")
Gear Train	Planetary
Winch Weight	27.5kg / 60.6lb (without rope)

### LINE PULL AND LINE SPEED Max 10,000lb, Pressure 175 bar, Flow 30 l/min

Layer of Rope		1	2	3	4	5
Max Line Pull (1:1)	lb	1,667	1,389	1,212	1,058	992
	kg	756	630	550	480	450
Max Line Pull (1:6)	lb	10,000	8,320	7,120	6,200	5,500
	kg	4,535	3,770	3,330	2,812	2,490
Line Speed (1:1)	FPM	134.5	161	183.7	209	223
	MPM	41	49	56	64	68
Line Speed (1:6)	FPM	21.3	26.2	30.5	36.1	37
	MPM	6.5	8	9.3	11	11.3

### DIMENSIONS (mm)

