


GOODWINCH Ltd also stock this very powerful TDS 10,000 lbs (4,535 Kgs) commercial hydraulic winch, which is very efficient and suitable for use with either wire rope or synthetic Dyneema® Bowrope



**The KHD-10 Goldfish Series
Twin Speed Variable Hydraulic Winch**



FEATURES

- Smooth running over the entire speed range
- Highly efficient, constant operating torque motor
- Rotating ring gear freespool clutch operated by pull and turn for rapid rope payout
- Freespooling. Power in /out. Mechanical Lock
- Stainless Steel Tie Bars
- Reversible mounting
- Supplied as a bare winch, for your choice of rope and fairleads

KHD-10 bare winch (no rope or fairleads)	£ 699
KHD-10 complete with 9.5mm x 27m wire rope and roller fairleads	£ 739
KHD-10 complete with 11mm x 27m Dyneema® Bowrope & Aluminium Hawse	£ 864



GOODWINCH LIMITED

East Foldhay, Zeal Monachorum, CREDITON,
Devon, EX17 6DH, England

Tel: 01363 82666 Fax: 01363 82782

E: sales@goodwinch.com W: www.goodwinch.com

AS MOST OF OUR BUSINESS IS UK & EUROPEAN 4x4 DEALERS AND OVERSEAS SALES, ALL PRICES ARE PLUS CARRIAGE AND VAT

 Simply brilliant, our versatile lightweight, easy to splice and handle
DYNEEMA® BOWROPE
 An immensely strong 12 strand synthetic winch rope made from Dyneema® SK75 High Modulus Polyethylene Fibre, manufactured to a very high exact specification set by David Bowyer of GOODWINCH LIMITED

Importers, Exporters, Wholesale Distributors and Retailers of Winches & Accessories

Dyneema® is a registered trademark of Royal DSM N.V.

Specification

Model	KHD-10
Line Pull	HIGH 1,667lb / 756kg
	LOW 10,000 / 4,535kg
Operation Pressure	175 bar / 2537 psi
Max Oil Flow	15.9 g/min (60 l/min)
Gear Ratio	FREE
	1:1 (HIGH)
	1:6 (LOW)
Wire Rope Size	9.5mm x 27.4m (3/8" x 90')
Drum Size	63.5mm x 215mm (2.5" x 8.4")
Gear Train	Planetary
Winch Weight	27.5kg / 60.6lb (without rope)

LINE PULL AND LINE SPEED Max 10,000lb, Pressure 175 bar, Flow 30 l/min

Layer of Rope		1	2	3	4	5
Max Line Pull (1:1)	lb	1,667	1,389	1,212	1,058	992
	kg	756	630	550	480	450
Max Line Pull (1:6)	lb	10,000	8,320	7,120	6,200	5,500
	kg	4,535	3,770	3,330	2,812	2,490
Line Speed (1:1)	FPM	134.5	161	183.7	209	223
	MPM	41	49	56	64	68
Line Speed (1:6)	FPM	21.3	26.2	30.5	36.1	37
	MPM	6.5	8	9.3	11	11.3

DIMENSIONS (mm)

